

LAVA® 2.0 STEEL & GLASS

With 2.0 you are plug & play ready.

The LAVA® 2.0 designer infrared heaters are particularly efficient and energy-saving. The 6 mm thick surface material made of safety glass, special ceramics or fi nestone, as well as two temperature limiters in all panels ensure safety in use at all times. Thanks to the innovative technology the surfaces are a very good radiation emitter. In conjunction with the even heat distribution on the surface, the optimally insulated rear guarantees a high radiation efficiency and thus maximum infrared heat radiation to the front of the room.

The frameless construction creates a modern design. Four surfaces (STEEL / GLASS / CERAMIC / STONE) and up to six outputs are available.

The practical plug & play box on the rear of all LAVA® 2.0 models makes it easy to install a controller, whether directly on the device, by radio or using a wired controller.



TECHNICAL DETAILS

- > Voltage: 230 V
- > IP rating: IP X4
- > IEC protection class: I
- > Connection: Connection cable (with plug) 1 m
- > Wall mounting: horizontally or vertically
- > Warranty: 5 years

BENEFITS OF THIS PRODUCT

- + Highest radiation efficiency due to
 - maximum forward radiation
 - homogeneous surface temperature
 - large surface
 - optimally insulated rear (approx. 40 °C for wall mounting)
- + Frameless Infinity design
- + Plug & play connection system for easy individual control
- + Highest safety against breakage and overheating
- + No service or maintenance required
- + Without magnetic field

TECHNICAL DETAILS



- > Output: 250, 500, 750, 1000 W
- > Surface temperature: max. 95 °C at standard internal temp.
- > Surface: steel sheet
- > Device/installation depth: 26/57 mm
- > Certification: TÜV

LAVA® STEEL 2.0 infrared heater, steel sheet, white (W) RAL 9016

PG: I1 | DT: ex stock

Type	Item no.	Output (W)	Length (mm)	Height (mm)	Weight (kg)
LAVA2-STEEL-250-W	39618	250	500	630	6
LAVA2-STEEL-500-W	39619	500	900	630	10
LAVA2-STEEL-750-W	39620	750	1300	630	14.5
LAVA2-STEEL-1000-W	39621	1000	1600	630	18

TECHNICAL DETAILS



- > Output: 250, 500, 600, 750, 800, 1000 W
- > Surface temperature: max. 95 °C at standard internal temp.
- > Surface: 6 mm ESG safety glass
- > Device/installation depth: 30/61 mm
- > Certification: TÜV



LAVA® GLAS 2.0, infrared heating, glass, pure white (PW)

PG: I2 | DT: ex stock

Type	Item no.	Output (W)	Length (mm)	Height (mm)	Weight (kg)
LAVA2-GLAS-250-PW	39625	250	500	630	8
LAVA2-GLAS-500-PW	39626	500	900	630	14
LAVA2-GLAS-600-PW	39627	600	1300	500	16
LAVA2-GLAS-750-PW	39628	750	1300	630	20
LAVA2-GLAS-800-PW	39629	800	1600	500	20
LAVA2-GLAS-1000-PW	39630	1000	1600	630	25

LAVA® GLAS 2.0, infrared heating, glass, mirror (MR)

PG: I2 | DT: 1-2 weeks

Type	Item no.	Output (W)	Length (mm)	Height (mm)	Weight (kg)
LAVA2-GLAS-250-MR	39650	250	500	630	8
LAVA2-GLAS-500-MR	39651	500	900	630	14
LAVA2-GLAS-600-MR	39652	600	1300	500	16
LAVA2-GLAS-750-MR	39653	750	1300	630	20
LAVA2-GLAS-800-MR	39654	800	1600	500	20
LAVA2-GLAS-1000-MR	39655	1000	1600	630	25